totalElement


SPECIFICATION SHEET
Part no. B12X12X110N40

Block Magnet

1/2 x 1/2 x 1/10 Inch (12.70 x 12.70 x 2.54 mm)

Width x Length x Thickness


ISOMETRIC VIEW — Not to scale



SPECIFICATIONS

WIDTH	0.500 Inch [12.70 mm]
LENGTH	0.500 Inch [12.70 mm]
THICKNESS	0.100 Inch [2.54 mm]
TOLERANCE	±0.004 Inch [±0.10 mm]
MATERIAL	Sintered Neodymium (NdFeB)
GRADE	N40
COATING	Nickel-Copper-Nickel (Ni-Cu-Ni)
MAGNETIZATION	Through the thickness
PULL FORCE	5.1 lbs (2.3 kg)
SURFACE FIELD	2,180 Gauss (218 mT)
WEIGHT (EACH)	3.1 g (0.11 oz)

DIMENSIONS — Inch [mm] · not to scale



MAGNETIZATION



Magnetized through the 0.100 [2.54] dimension. Pole faces shown for illustration.

GRADE PROPERTIES · N40

PROPERTY	SI	CGS / IMPERIAL
Remanence (Br)	1.25–1.28 T	12.5–12.8 kG
Coercivity (Hcb)	≥ 907 kA/m	≥ 11.4 kOe
Intrinsic coercivity (Hcj)	≥ 955 kA/m	≥ 12 kOe
Max. energy product (BH)max	302–326 kJ/m³	38–41 MGOe
Max. operating temperature	80 °C	176 °F

Typical values for sintered NdFeB of grade N40 at room temperature, not measured on this part. The highest safe working temperature also depends on the magnet's shape and how it's used.

Handling: neodymium magnets are brittle and can chip, or pinch skin, if they snap together. Keep them away from pacemakers and magnetic media.

VIEW ONLINE

Scan to open this magnet on totalElement.com.

CAD FILES

The technical drawing and 3D model are on the product page.

totalElement
totalElement.com
help@totalelement.com
1 (855) 328-2822