


Cube Magnet

1/8 x 1/8 x 1/8 Inch (3.18 x 3.18 x 3.18 mm)



Width x Length x Thickness

ISOMETRIC VIEW

Not to scale

**SPECIFICATIONS**

WIDTH	0.125 Inch [3.18 mm]
LENGTH	0.125 Inch [3.18 mm]
THICKNESS	0.125 Inch [3.18 mm]
TOLERANCE	±0.004 Inch [±0.10 mm]
MATERIAL	Sintered Neodymium (NdFeB)
GRADE	N52
COATING	Nickel-Copper-Nickel (Ni-Cu-Ni)
MAGNETIZATION	Through the thickness
PULL FORCE	1.1 lbs (0.5 kg)
SURFACE FIELD	6,450 Gauss (645 mT)
WEIGHT (EACH)	0.2 g (0.0071 oz)

DIMENSIONS Inch [mm] · not to scale**MAGNETIZATION**

Magnetized through the 0.125 [3.18] dimension. Pole faces shown for illustration.

GRADE PROPERTIES · N52

PROPERTY	SI	CGS / IMPERIAL
Remanence (Br)	1.43–1.48 T	14.3–14.8 kG
Coercivity (Hcb)	≥ 836 kA/m	≥ 10.5 kOe
Intrinsic coercivity (Hcj)	≥ 876 kA/m	≥ 11 kOe
Max. energy product (BH)max	398–422 kJ/m ³	50–53 MGOe
Max. operating temperature	80 °C	176 °F

Typical values for sintered NdFeB of grade N52 at room temperature, not measured on this part. The highest safe working temperature also depends on the magnet's shape and how it's used.

Handling: neodymium magnets are brittle and can chip, or pinch skin, if they snap together. Keep them away from pacemakers and magnetic media.

**VIEW ONLINE**Scan to open this magnet on
totalElement.com.**CAD FILES**The technical drawing and 3D model are on the
product page.**totalElement**totalElement.com
help@totalelement.com
1 (855) 328-2822