totalElement

SPECIFICATION SHEET
Part no. D8X10MMN35

Disc Magnet

8 x 10 mm (0.3150 x 0.3937 Inch)

Diameter x Thickness


ISOMETRIC VIEW — Not to scale



SPECIFICATIONS

DIAMETER	8.00 mm [0.3150 Inch]
THICKNESS	10.00 mm [0.3937 Inch]
TOLERANCE	±0.10 mm [±0.004 Inch]
MATERIAL	Sintered Neodymium (NdFeB)
GRADE	N35
COATING	Nickel-Copper-Nickel (Ni-Cu-Ni)
MAGNETIZATION	Axially, through the thickness
PULL FORCE	4.9 lbs (2.2 kg)
SURFACE FIELD	5,617 Gauss (562 mT)
WEIGHT (EACH)	3.8 g (0.13 oz)


DIMENSIONS mm [Inch] · not to scale



TOP VIEW

FRONT VIEW

MAGNETIZATION



Axially magnetized through the 10.00 [0.3937] thickness. Pole faces shown for illustration.

GRADE PROPERTIES · N35

PROPERTY	SI	CGS / IMPERIAL
Remanence (Br)	1.17–1.22 T	11.7–12.2 kG
Coercivity (Hcb)	≥ 859 kA/m	≥ 10.8 kOe
Intrinsic coercivity (Hcj)	≥ 955 kA/m	≥ 12 kOe
Max. energy product (BH)max	263–287 kJ/m³	33–36 MGOe
Max. operating temperature	80 °C	176 °F

Typical values for sintered NdFeB of grade N35 at room temperature, not measured on this part. The highest safe working temperature also depends on the magnet's shape and how it's used.

Handling: neodymium magnets are brittle and can chip, or pinch skin, if they snap together. Keep them away from pacemakers and magnetic media.

VIEW ONLINE

Scan to open this magnet on totalElement.com.

CAD FILES

The technical drawing and 3D model are on the product page.

totalElement
totalElement.com
help@totalelement.com
1 (855) 328-2822