


Ring Magnet

30 x 10 x 3 mm (1.1811 x 0.3937 x 0.1181 Inch)



Diameter x Inner Diameter x Thickness

ISOMETRIC VIEW

Not to scale

**SPECIFICATIONS**

DIAMETER	30.00 mm [1.1811 Inch]
INNER DIAMETER	10.00 mm [0.3937 Inch]
THICKNESS	3.00 mm [0.1181 Inch]
TOLERANCE	±0.10 mm [±0.004 Inch]
MATERIAL	Sintered Neodymium (NdFeB)
GRADE	N35
COATING	Nickel-Copper-Nickel (Ni-Cu-Ni)
MAGNETIZATION	Axially, through the thickness
PULL FORCE	11.2 lbs (5.1 kg)

DIMENSIONS mm [Inch] · not to scale**MAGNETIZATION**

Axially magnetized through the 3.00 [0.1181] thickness. Pole faces shown for illustration.

GRADE PROPERTIES · N35

PROPERTY	SI	CGS / IMPERIAL
Remanence (Br)	1.17–1.22 T	11.7–12.2 kG
Coercivity (Hcb)	≥ 859 kA/m	≥ 10.8 kOe
Intrinsic coercivity (Hcj)	≥ 955 kA/m	≥ 12 kOe
Max. energy product (BH)max	263–287 kJ/m ³	33–36 MGOe
Max. operating temperature	80 °C	176 °F

Typical values for sintered NdFeB of grade N35 at room temperature, not measured on this part. The highest safe working temperature also depends on the magnet's shape and how it's used.

Handling: neodymium magnets are brittle and can chip, or pinch skin, if they snap together. Keep them away from pacemakers and magnetic media.

**VIEW ONLINE**

Scan to open this magnet on
totalElement.com.

CAD FILES

The technical drawing and 3D model are on the
product page.

totalElement

totalElement.com
help@totalelement.com
1 (855) 328-2822